

# Carbon-Ti X-CarboCam EVO 50 x 110




**ITALIANO**

## CARATTERISTICHE

La X-CarboCam EVO 50 x 110 è una corona asimmetrica realizzata in fibra di carbonio (struttura interna), lega di alluminio 7075-T6 (dentatura) e titanio grado 5 (elementi per la risalita catena). La particolare forma a geometria variabile consente un più rapido superamento dei punti morti della pedalata e determina una spinta più efficace e potente. Dopo un necessario periodo di adattamento si avverte una pedalata più rotonda e redditizia. La speciale dentatura è stata studiata per lavorare in sincronia con la corona Carbon-Ti X- RoadCam EVO 36 x 110, si sconsiglia di accoppiare la corona X-CarboCam EVO 50 x 110 con corone di misura o marca differente, in modo da non comprometterne le performance di cambiata. La corona presenta cinque fori con giro bulloni 110 mm ed è compatibile con pedivelle compact come THM Clavicula SE or Quarq Dzero. Compatibile con i gruppi Shimano Dura-Ace 9200, Ultegra 8100 e tutti i gruppi precedenti 11 velocità. Non compatibile con i gruppi SRAM AXS 12 velocità.

## PRIMA DI INIZIARE

Per il montaggio munirsi di una chiave per il serraggio delle viti (Torx T30 e esagonale 6mm) e frenafiletti medio blu (es. Loctite 242). Per il fissaggio della corona alla pedivella si consiglia il kit Carbon-Ti X-Fix ROAD. Nel caso non si posseggano alcuni degli attrezzi necessari, si consiglia di rivolgersi al proprio meccanico qualificato di fiducia.





## INSTALLAZIONE

Installare la corona X-CarboCam EVO 50 x 110 nella posizione più esterna della guarnitura (Fig.A).

Fissare la corona orientandola in modo tale che il segno di riferimento sia allineato alla pedivella. Allineare la corona interna nello stesso modo, nella posizione interna della guarnitura (Fig.B).

Applicare una goccia di frenafiletti medio sul filetto viti di fissaggio e serrarle con una coppia di serraggio di 6 Nm.

Posizionare il deragliatore 2-3 mm sopra al raggio massimo di ingombro della corona esterna (Fig.C) e settare i fine corsa in modo da evitare cadute della catena esterne o interne. Per una migliore performance, si consiglia di montare una catena nuova. Verificare periodicamente il corretto serraggio delle viti di fissaggio della corona.



## GARANZIA

I prodotti Carbon-Ti sono garantiti contro difetti di materiale e costruzione per un periodo di 2 anni dalla data di acquisto del primo utilizzatore, certificata dallo scontrino fiscale del negozio. La garanzia decade nel caso in cui la manutenzione ordinaria o straordinaria consigliata non sia stata eseguita.

In caso di vizio, Carbon-Ti si impegna ad effettuare la sostituzione o la riparazione, a sua discrezione dell'elemento riconosciuto difettoso.

Per essere accettato, il difetto deve essere comunicato dal primo proprietario al proprio rivenditore e da quest'ultimo, dopo averlo verificato, alla Carbon-Ti.

La garanzia non copre i danni risultanti da trasporto, giacenza, incidenti, negligenze, colpi o cadute, mancato rispetto delle informazioni del libretto istruzioni, montaggio errato o con prodotti non compatibili, cattiva manutenzione, usura normale, modifiche o alterazioni del prodotto.

La Garanzia non copre le parti soggette a normale usura.

**X-CarboCam EVO 50 x 110 è 100% made in Italy**



Via per Ospitaletto, 147 25046 Cazzago S.Martino (Brescia) – ITALY  
Web site: <http://www.carbon-ti.com> Email: [info@carbon-ti.com](mailto:info@carbon-ti.com)

# Carbon-Ti X-CarboCam EVO 50 x 110



**ENGLISH**

## FEATURES

The X-CarboCam EVO 50 x 110 is an asymmetric single-chainring realized in carbon fiber (inner body), AL7075-T6 aluminium alloy (teeth) and titanium grade 5 (up-shifting elements). The special variable geometry allows a quicker overcoming of the dead spots and provides a more efficient and powerful pedal stroke.

After a necessary period of adjustment, you can feel a smoother and profitable pedaling.

The special teeth has been designed to work in synchrony with the inner Carbon-Ti X-RoadCam EVO 36 x 110. It is not recommended to pair the X-CarboCam EVO 50 x 110 with a different size or with products of other brands, in order not compromise the shifting performance.

The chainring has a 110 mm BCD with five fixing holes and is compatible with compact 5 arms cranksets like THM Clavicula SE or Quarq Dzero.

Compatible with Shimano Dura-Ace 9200, Ultegra 8100 and all previous 11-speed groupsets.


Not compatible with SRAM AXS 12 speed groups.

## BEFORE YOU START

It is useful to have a key for the tightening (Torx T30 and hexagonal 6mm) and a medium strength threadlocker (eg. Loctite 242).

For the fixing of the chainring, it is recommended to use the Carbon-Ti X-Fix ROAD bolt kit.

If you don't have any of these necessary tools, you should consult your preferred skilled mechanic.



## INSTALLATION

Put the X-CarboCam EVO 50 x 110 chainring in the outer position of the crankset (Fig. A).



Position the chainring so that the alignment guide is located behind the crank arm. Make the same thing with the inner chainring, in the inner position of the crankset (Fig. B).

Apply a drop of medium strength threadlocker on the threads of the fixing bolts and tighten them with a tightening torque of about 6 Nm.

Position the front derailleur 2-3 mm above the maximum footprint of the outer ring (Fig.D) and set the end of stroke, to prevent external or internal chain falls.

For better performance we recommend to mount a new chain with the new chainring.

Check the tightening of the fixing bolts periodically.



## WARRANTY

Carbon-Ti products are guaranteed against any defects for a period of 2 years from the date of purchase by the first owner, registered by the dealer.

The warranty decays in absence of the recommended regular or extraordinary maintenance.

In case of defects, Carbon-Ti will replace or repair, at its own discretion, the recognized defective part. To be accepted, the defect must be communicated to Carbon-Ti through the dealer/importer after his own control. If Carbon-Ti checking reveals that the damage is due to one of the reasons mentioned in the following paragraph, the replacement won't be accepted and the defective item will be sent back to the owner at his own charge.

The guarantee does not cover damage resulting from transportation, warehousing, accidents, negligence, impact or falls, non-compliance with the information in the instruction manuals, assembly errors and assembly using non-compatible products, bad maintenance, modifications or alterations of the product.

The guarantee does not cover parts and components subject to normal wear.

**X-CarboCam EVO 50 x 110 is 100% made in Italy**



Via per Ospitaletto, 147 25046 Cazzago S.Martino (Brescia) – ITALY  
Web site: <http://www.carbon-ti.com> Email: [info@carbon-ti.com](mailto:info@carbon-ti.com)